



Installation Instructions

Inline Fluoride Reduction System

Please ensure you have read the instructions and that no parts are missing prior to installation.

Please note:

This cartridge has been preflushed to minimize sediment deposits in the secondary filter. Please re-flush water through this filter for 30 seconds before fitting to the carbon filter as this may cause blockage.

The approximate life of your filter is one year and will vary depending on several factors, i.e. manufacturers recommendation, amount of water being used through the filter, turbid water supply, amount of sediment in the water etc. If the flow through the filter decreases or water taste deteriorates it may be time to replace the filter.

How do you know when it's time to replace your cartridge? We place your name in our records; this allows us to remember when you received your new cartridge. We will then remind you when it is time to replace it.

For support please phone our technical support team on 0800 787 342

Step one

Turn water supply off at tapping valve or main water supply. Tapping valve is the fitting used to connect your water purifier to the water pipe.

Step two

After turning the tapping valve off, turn on the purifier tap until the flow of water stops. This will confirm that your water has been turned off at the tapping valve and the water line has been drained of any remaining water.

Step three

Find a suitable position for the fluoride reducing filter, and install the bracket somewhere between the tapping valve and CI251 inline filter or HU14 housing unit.

Step four

Screw the John Guest fittings into each end of the fluoride reducing filter (if not already fitted), please ensure there is plumbers tape on the thread of these fittings.

Step five

Remove the tubing from the entry point of your carbon filter by pushing in on the collet (small round sleeve) and insert it in the entry point of the fluoride reducing filter. Then insert the extra length of tubing supplied into the fluoride reducing filters outlet and the other end into the carbon filters inlet. You might need to trim tubing to suit the space under your bench. Ensure you make a straight, clean cut if trimming the tubing.

Step six

Turn water supply on and run filter for approximately 5 minutes to activate the filter. The water may have a milky look for the first few hours; this is due to millions of air bubbles being forced from the cartridge.